SKODA OCTAVIA OCTAVIA SUPER 703 (1961-1963)



ENGINE Capacity: 2,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	

Change every 2000 km

DIFFERENTIAL REAR Capacity: 1,4 liter		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 2000 km, change every 8000	km	

TRANSMISSION 4/1 Capacity: 0,7 liter		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 2000 km, change every 8000) km	

HYDRAULIC BRAKE SYSTEM Capacity: 0,6 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Drauliquid DOT 3	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 2000 km

SKODA OCTAVIA OCTAVIA SUPER 703 (1961-1963)



WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 8000 km

WHEEL BEARINGS REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 16000 km

COOLING SYSTEM Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

STEERING BOX Capacity: 0,25 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 2000 km, change every 800	km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.