SUBARU (EU) LEONE/L SERIES LEONE 1400 (1973-1977)



| ENGINE EA63 Capacity: 3,3 liter | | |
|------------------------------------|---------------------------|---------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Classic Racing Oil 15W-50 | Classic Multigrade 15W-40 | Classic Multigrade 10W-30 |
| Change every 5000 km/ 3 months | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Classic Racing Oil 15W-50 | Classic Multigrade 15W-40 | Classic Multigrade 10W-30 |
| | 1 | 1 |

Change every 1500 km

| TRANSAXLE MANUAL 4/1 Capacity: 2,5 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Gear EP 90 | |
| Check every 5000 km, change every 800 | 100 km |
| | CLIMATE |

| USE | CLIMATE |
|--------------------------|----------|
| Initial service | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Gear EP 90 | |
| Change every 1500 km | · |

| HYDRAULIC BRAKE SYSTEM | |
|---------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |
| Change aver 20000 km/ 10 manths | |

Change every 20000 km/ 12 months

SUBARU (EU) LEONE/L SERIES LEONE 1400 (1973-1977)



| GREASE POINTS/NIPPLES WHEEL BEARINGS | | | |
|--------------------------------------|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

Change every 40000 km/ 24 months

| COOLING SYSTEM Capacity: 6 liter | | | |
|-------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant -38 Organic NF | Coolant -26 | | |
| Change avery 10000 km/21 months | · · · | · | |

Change every 40000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.