

PRODUCT RECOMMENDATION

# SUZUKI SC SS20 SC 100 GX SS20 (1978-1983)



**ENGINE F10A**  
Capacity: 3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Classic Racing Oil 15W-50</b>	<b>Classic Multigrade 20W-50</b>

*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Classic Multigrade 15W-40</b>	<b>Classic Multigrade 10W-30</b>

*Change every 10000 km/ 6 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Classic Racing Oil 15W-50</b>	<b>Classic Multigrade 20W-50</b>

*Change every 1000 km*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Classic Multigrade 15W-40</b>	<b>Classic Multigrade 10W-30</b>

*Change every 1000 km*

**TRANSAXLE MANUAL 4/1**  
Capacity: 1,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Classic Gear MP 90</b>	

*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	
<b>Classic Gear EP 90</b>	

*Change every 1000 km*

**SUZUKI SC SS20 SC 100 GX SS20 (1978-1983)****HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

**COOLING SYSTEM**

Capacity: 7,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10000 km/ 6 months, change every 40000 km/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*