

TOYOTA COROLLA E COROLLA 1800 (59 KW) TE72 (1979-1983)

**ENGINE 3T**

Capacity: 4,2 liter (Dry fill), Capacity: 3,8 liter (Service fill), Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Racing Oil 15W-50	Classic Multigrade 20W-50

Change every 1000 km

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 15W-40	Classic Multigrade 10W-30

Change every 1000 km

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Racing Oil 15W-50	Classic Multigrade 20W-50

Change every 10000 km/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Classic Multigrade 15W-40	Classic Multigrade 10W-30

*Change every 10000 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube RPC 75W-80	SP Gear 5015

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TOYOTA COROLLA E COROLLA 1800 (59 KW) TE72 (1979-1983)



DIFFERENTIAL REAR LIMITED SLIP

Capacity: 1,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TRANSMISSION AUTOMATIC 3/1

Capacity: 6,3 liter (Dry fill), Capacity: 2,4 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF F		

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

TRANSMISSION MANUAL 5/1

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Gear EP 90	Classic Gear EP 80	

Check every 10000 km/ 6 months, change every 40000 km/ 24 months

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 20000 km/ 12 months

HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Change every 20000 km/ 12 months

TOYOTA COROLLA E COROLLA 1800 (59 KW) TE72 (1979-1983)



GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

Change every 40000 km/ 24 months

WHEEL BEARINGS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 40000 km/ 24 months

COOLING SYSTEM

Capacity: 7,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 20000 km/ 12 months

STEERING BOX

Capacity: 0,21 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		

Check every 20000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.