

TRIUMPH SPITFIRE SPITFIRE 4 (1962-1965)



ENGINE

Capacity: 4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Multigrade 15W-40*Change every 3000 miles/ 4800 km*

DIFFERENTIAL REAR

Capacity: 0,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 9600 km/ 6000 miles, change every 19200 km/ 12000 miles*

TRANSMISSION MANUAL 4/1

Capacity: 0,9 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 9600 km/ 6000 miles, change every 19200 km/ 12000 miles*

HYDRAULIC BRAKE SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

COOLING SYSTEM

Capacity: 5,3 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.