VAUXHALL VIVA VIVA 1.6 HC HB (1968-1970)



ENGINE Capacity: 4,83 liter (Dry fill), Capacity: 4,69	liter (Service fill)	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Multigrade 15W-40		
Check every 750 km, change every 10000	km/ 3 months	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Classic Multigrade 10W-30		
Check every 750 km, change every 10000	km/ 3 months	
AXLE REAR Capacity: 0,71 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 20000 km/ 6 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
Check every 20000 km/ 6 months		
TRANSMISSION MANUAL 4/1		
Capacity: 1,36 liter		

Supucity: 1,00 ittel		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Gear ZC 90		
Check every 20000 km/ 6 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
Check every 20000 km/ 6 months		

VAUXHALL VIVA VIVA 1.6 HC HB (1968-1970)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Check every 10000 km/3 months		

GREASE POINTS/NIPPLES		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Change every 50000 km/ 30 months	<u>'</u>	

WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50000 km/ 30 month	78	

COOLING SYSTEM Capacity: 7,39 liter, Capacity: 7,95 liter (+ heater)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant -38 Organic NF	Coolant -26		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.