VOLKSWAGEN (VW) (EU) BEETLE / TYPE 1 1200 (1973-1978)



ENGINE Capacity: 2,5 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 5000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40
Change every 5000 km/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	HDX 10W	
Change every 5000 km/ 6 months		

TORQUE CONVERTER SEMI-AUTOMATIC TRANSAXLE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic ATF A		

TRANSAXLE MANUAL 4/1 Capacity: 2-2,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 5000 km, change every 2500	0 km	

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		
Check every 5000 km, change every 25000 km		

VOLKSWAGEN (VW) (EU) BEETLE / TYPE 1 1200 (1973-1978)



TRANSAXLE SEMI-AUTOMATIC 3/1		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 5000 km, change every 2500	0 km	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Classic Gear EP 80		

Check every 5000 km, change every 25000 km

HYDRAULIC BRAKE SYSTEM Capacity: 250 CM3	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

STEERING BOX Capacity: 125 CM3	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear MP 90	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.