VOLKSWAGEN (VW) (EU) GOLF I TYPE 17 GOLF 1.5 (51 KW) (1980-1983)



USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Classic Monograde 50		
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Classic Racing Oil 15W-50	Classic Multigrade 20W-50	Classic Multigrade 15W-40
Change every 10000 km/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	HDX 10W	

DIFFERENTIAL FROM AUTOMATIC		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

Classic Gear EP 90	Classic Gear EP 80		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
TRANSAXLE MANUAL 4+E 5/1			

TRANSAXLE MANUAL 4/1 Capacity: 1,25 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Classic Gear EP 90	Classic Gear EP 80		

VOLKSWAGEN (VW) (EU) GOLF I TYPE 17 GOLF 1.5 (51 KW) (1980-1983)



TRANSMISSION AUTOMATIC 3/1 Capacity: 6 liter (Dry fill), Capacity: 3 liter (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 45000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Change every 30000 km		
HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		

сымате Moderate

COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

USE

Normal

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Change every 24 months