

VOLKSWAGEN (VW) (EU) TRANSPORTER / TYPE 2 T1/T2 TRANSPORTER/BUS 1600 T2 (1967-1971)

**ENGINE**

Capacity: 2,5 liter (Service fill)

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Classic Monograde 50***Change every 5000 km/ 6 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Multigrade 10W-30****PRODUCT RECOMMENDATION 2****Classic Monograde 30***Change every 5000 km/ 6 months***USE**

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Classic Monograde 50***Change every 1000 km***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Classic Multigrade 10W-30****PRODUCT RECOMMENDATION 2****Classic Monograde 30***Change every 1000 km*

VOLKSWAGEN (VW) (EU) TRANSPORTER / TYPE 2 T1/T2 TRANSPORTER/BUS 1600 T2 (1967-1971)

**TRANSAXLE MANUAL 4/1**

Capacity: 3,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Check every 10000 km, change every 50000 km*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Check every 10000 km, change every 50000 km*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Gear EP 90*Change every 1000 km*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

Classic Gear EP 80*Change every 1000 km***GREASE POINTS/NIPPLES**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 2

MP Lithep Grease EP 2*Change every 10000 km/ 12 months***WHEEL BEARINGS FRONT**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 2

MP Lithep Grease EP 2*Change every 50000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.