

| ENGINE B16A Capacity: 3,5 liter | | | |
|------------------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Classic Multigrade 10W-30 | Classic Monograde 30 | | |
| | | | |

Check every 500 km, change every 5000 km

| DIFFERENTIAL REAR Capacity: 1,3 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Classic Gear MP 90 | Gearlube RPC 75W-80 | SP Gear 5015 |

Check every 5000 km, change every 20000 km

| TRANSMISSION MANUAL H6 3/1 Capacity: 0,9 liter | | |
|---|------|----------|
| USE | | CLIMATE |
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Gear ZC 90 | | |
| Check every 5000 km, change every 2000 | 0 km | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |

Classic Gear EP 80

Check every 5000 km, change every 20000 km

| HYDRAULIC BRAKE SYSTEM | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |
| | |

VOLVO (EU) 121/122S/220/AMAZON 121 (1956-1958)



| GREASE POINTS/NIPPLES OTHERS | | |
|------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 5000 km

| GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| Change aver 20000 km | 1 | 1 |

Change every 20000 km

| GREASE POINTS/NIPPLES WHEEL BEARINGS REAR | | |
|---|--------------------------|--|
| | CLIMATE | |
| | Moderate | |
| PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |
| | PRODUCT RECOMMENDATION 2 | |

Change every 40000 km/ 12 months

| COOLING SYSTEM Capacity: 8,5 liter | | |
|---------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.