

VOLVO (EU) 240 245 GL B21A (1979-1984)**ENGINE B21A**

Capacity: 3,85 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Monograde 50	Classic Monograde 30	

Change every 10000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Classic Racing Oil 15W-50	Classic Multigrade 20W-50

Change every 10000 km/ 12 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Monograde 50	Classic Monograde 30	

Change every 5000 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Asyntho 5W-30	Classic Racing Oil 15W-50	Classic Multigrade 20W-50

*Change every 5000 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Classic Gear MP 90		

*Check every 10000 km***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Classic Gear LS 90		

Check every 10000 km

VOLVO (EU) 240 245 GL B21A (1979-1984)**TRANSMISSION AUTOMATIC BW55 3/1**

Capacity: 6,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF F*Check every 10000 km/ 6 months***TRANSMISSION MANUAL M45 4/1**

Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF F*Check every 10000 km***TRANSMISSION MANUAL + OVERDRIVE M46 5/1**

Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF F*Check every 10000 km***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 36 months***POWER STEERING**

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

PRODUCT RECOMMENDATION 2

Classic ATF A

PRODUCT RECOMMENDATION 3

Classic ATF F*Check every 10000 km*

VOLVO (EU) 240 245 GL B21A (1979-1984)**COOLING SYSTEM**

Capacity: 9,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

*Change every 24 months***CARBURETTOR DAMPER**

Capacity: 0-0 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 10000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.