

VOLVO (EU) 260 264 DL (1974-1975)**ENGINE B27E**

Capacity: 6,5 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 20W-50

PRODUCT RECOMMENDATION 2

Classic Monograde 30*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 3

Classic Multigrade 10W-30*Change every 10000 km/ 6 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

HDX 10W*Change every 10000 km/ 6 months*

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Classic Multigrade 20W-50

PRODUCT RECOMMENDATION 2

Classic Monograde 30*Change every 5000 km/ 6 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Classic Racing Oil 15W-50

PRODUCT RECOMMENDATION 2

Classic Multigrade 15W-40

PRODUCT RECOMMENDATION 3

Classic Multigrade 10W-30*Change every 5000 km/ 6 months*

USE	CLIMATE
Severe	Arctic

PRODUCT RECOMMENDATION 1

HDX 10W*Change every 5000 km/ 6 months*

VOLVO (EU) 260 264 DL (1974-1975)**DIFFERENTIAL REAR**

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear MP 90*Check every 10000 km***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic Gear LS 90*Check every 10000 km***TRANSMISSION AUTOMATIC BW55 3/1**

Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Classic ATF F*Check every 10000 km***TRANSMISSION MANUAL M50 4/1**

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Vintage Gear 90*Check every 10000 km, change every 40000 km***TRANSMISSION MANUAL M51 5/1**

Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Vintage Gear 90*Check every 10000 km, change every 40000 km*

VOLVO (EU) 260 264 DL (1974-1975)**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Change every 36 months***HYDRAULIC CLUTCH SYSTEM**

Capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3**POWER STEERING**

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

PRODUCT RECOMMENDATION 2

Classic ATF A

PRODUCT RECOMMENDATION 3

Classic ATF F*Check every 10000 km***COOLING SYSTEM**

Capacity: 10,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.