WOLSELEY 15/60, 16/60 15/60 (1958-1961)



ENGINE B Capacity: 4,25 liter	
USE	CLIMATE
Normal	Mediterranean
PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	
Change every 5000 km	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	
Change every 5000 km	
USE	CLIMATE
Initial service	Mediterranean
PRODUCT RECOMMENDATION 1	
Classic Multigrade 10W-30	
Change every 800 km	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Classic Monograde 30	
Change every 800 km	
DIFFERENTIAL Capacity: 1,28 liter	
USE	 CLIMATE
Normal	Moderate

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Classic Gear EP 90		
Check every 1500 km, change every 9000 km		

TRANSMISSION MANUAL 4/1 Capacity: 2,56 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Classic Multigrade 10W-30	Classic Monograde 30	
Check every 1500 km, change every 9000 km		

WOLSELEY 15/60, 16/60 15/60 (1958-1961)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3			
Charles a variety 4500 km			

Check every 1500 km

HYDRAULIC CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 1500 km	·

GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 15000 km		

COOLING SYSTEM Capacity: 7,09 liter (+ heater)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 8000 km	'	

CARBURETTOR DAMPER		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Classic Monograde 30		

WOLSELEY 15/60, 16/60 15/60 (1958-1961)



STEERING BOX	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Classic Gear EP 90	
Check every 1500 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.