ACURA (USA / CAN) CSX CSX 2.0 (CAN) (2006-2011)



ENGINE K20Z2 Capacity: 5,3 liter (Dry fill), Capacity: 4,2 liter (Service fill), Filter capacity: 0,2 liter				
USE		CLIMATE		
Flexible (on board maintenance syst	em)	Moderate		
PRODUCT RECOMMENDATION 1				
Duranza ECO 5W-20				

TRANSAXLE AUTOMATIC 5/1 Capacity: 5,9-6,5 liter (Dry fill), Capacity: 2,4-2,9 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4026				

TRANSAXLE MANUAL 5/1 Capacity: 1,7 liter (Dry fill), Capacity: 1,5 liter (Service fill)				
use Normal		climate Moderate		
PRODUCT RECOMMENDATION 1 SP Gear 5015				

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		

Check every 1 months, change every 36 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3		

Check every 1 months, change every 36 months

ACURA (USA / CAN) CSX CSX 2.0 (CAN) (2006-2011)



COOLING SYSTEM Capacity: 6,45-6,6 liter (Dry fill), Capacity: 0,4 liter (Reserve tank), Capacity: 4,2-4,3 liter (Service fill) USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 Coolant SP 14+

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.