ACURA (USA / CAN) ILX DE2 ILX 2.4 I-VTEC (CAN) (2015-2022)



ENGINE K24V7 Capacity: 4,4 liter (Service fill), Filter capa	city: 0,2 liter	
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		
Change every 12 months		
TRANSAXLE SEMI-AUTOMATIC DCT N Capacity: 3,9 liter	M4JA 8/1	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		
Change every 48000 km		
USE		CLIMATE
Severe, first change only		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		
Change every 64000 km		
USE		CLIMATE
Flexible (on board maintenance sys	tem)	Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		
HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 36 months		
COOLING SYSTEM		

COOLING SYSTEM Capacity: 6,5 liter		
USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		
		'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

PRODUCT RECOMMENDATION

ACURA (USA / CAN) ILX DE2 ILX 2.4 I-VTEC (CAN) (2015-2022)



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.