ACURA (USA / CAN) TSX CU2 TSX 3.5 (USA) (2009-2010)



ENGINE J35Z6 Capacity: 5 liter (Dry fill), Capacity: 4,3 liter	(Service fill)	
USE		CLIMATE
Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
Presteza MSP 0W-20		

TRANSAXLE AUTOMATIC 5/1 Capacity: 7,5 liter (Dry fill), Capacity: 3,3 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

COOLING SYSTEM Capacity: 6,7 liter (Service fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.