

ALFA ROMEO (EU) 155 167 155 2.0 TD (1993-1997)



ENGINE

Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40*Check every 500 km, change every 10000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30*Check every 500 km, change every 10000 km/ 12 months*

TRANSAXLE MANUAL 5/1

Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Check every 40000 km, change every 120000 km*

HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 500 km, change every 12 months*

POWER STEERING

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 500 km*

ALFA ROMEO (EU) 155 167 155 2.0 TD (1993-1997)

**COOLING SYSTEM**

Capacity: 8,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 500 km, change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.