

# ALFA ROMEO (EU) GT 937 GT 3.2 V6 (2004-2008)



**ENGINE** 936A000  
Capacity: 5,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Emperol Racing 10W-60**

*Change every 20000 km*

**TRANSAXLE MANUAL** 5/1  
Capacity: 2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1071**

PRODUCT RECOMMENDATION 2

**Syngear 75W-90**

*Check every 80000 km*

**TRANSAXLE MANUAL** 6/1  
Capacity: 2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

PRODUCT RECOMMENDATION 3

**Syngear 75W-90**

*Check every 80000 km*

**GEAR OPERATING SYSTEM** Selespeed  
Capacity: 0,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Fluid 3023**

*Check every 20000 km*

**HYDRAULIC BRAKE/CLUTCH SYSTEM** ABS  
Capacity: 0,52 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

*Check every 20000 km, change every 60000 km/ 24 months*

# ALFA ROMEO (EU) GT 937 GT 3.2 V6 (2004-2008)



## POWER STEERING

Capacity: 1,2 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**ATF Dexron II-D**

Check every 20000 km

## COOLING SYSTEM

Capacity: 9,2 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

## PRODUCT RECOMMENDATION 2

**Coolant SP 12**

## PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF**

Check every 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.