ALFA ROMEO (EU) MITO 955 MITO 1.3 JTDM-2 (70 KW) (2015-2020)



| | • |
|--|---------------------|
| Avanza MSP 0W-30 | |
| PRODUCT RECOMMENDATION 1 | |
| Severe | Moderate |
| USE | CLIMATE |
| Change every 24 months | |
| PRODUCT RECOMMENDATION 1 Avanza MSP 0W-30 | |
| use Flexible (max) | climate Moderate |
| ENGINE 330A1000 Capacity: 3,9 liter, Filter capacity: 0,2 liter | |

Change every 12 months

| TRANSAXLE MANUAL 6/1 Capacity: 1,8 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1081 | SP Gear 5015 | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.) | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |
| 01 1000001 (10 11 | | |

Change every 40000 km/ 48 months

| COOLING SYSTEM Capacity: 7,2 liter | |
|---------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 14+ | |
| Check every 30000 km | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.