

AUDI (EU) 100, S4 100 2.6E (1992-1994)

ENGINE ABC
Capacity: 5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Helar 0W-40

Change every 15000 km/ 12 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Presteza MSP 5W-30		

Change every 15000 km/ 12 months

DIFFERENTIAL FROM AUTOMATIC
Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 15000 km/ 12 months

TRANSAXLE MANUAL 5/1
Capacity: 2,35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 15000 km/ 12 months

TRANSMISSION AUTOMATIC 4/1
Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 30000 km/ 12 months, change every 60000 km/ 48 months

AUDI (EU) 100, S4 100 2.6E (1992-1994)**HYDRAULIC SYSTEM POWER STEERING/LEVELLING**

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 24 months***POWER STEERING**

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.