

PRODUCT RECOMMENDATION

AUDI (EU) A3, S3 CABRIOLET 8V7 A3 CABRIOLET 1.8 TFSI QUATTRO (132 KW) (2014-2016)



ENGINE CJSB
Capacity: 5,2 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1 Helar SP LL-03 5W-30		
---	--	--

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Helar 0W-40	PRODUCT RECOMMENDATION 2 Emperol 5W-40	PRODUCT RECOMMENDATION 3 Asyntho 5W-30
--	--	--

Change every 15000 km/ 12 months

BEVEL GEAR
Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	
---	---	--

DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 SP Gear 1011	PRODUCT RECOMMENDATION 2 Syngear TDL 75W-90	
---	---	--

TRANSAXLE SEMI-AUTOMATIC S TRONIC 0D9 6/1
Capacity: 6,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 SP Matic 2072		
--	--	--

Change every 60000 km

AUDI (EU) A3, S3 CABRIOLET 8V7 A3 CABRIOLET 1.8 TFSI QUATTRO (132 KW) (2014-2016)



HYDRAULIC ACTUATION CONVERTIBLE ROOF

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HALDEX-CLUTCH

Capacity: 0,66 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 6036		

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.