AUDI (EU) A3, S3, RS 3 8P A3 1.2 TFSI (2010-2013)



Helar 0W-40	Emperol 5W-40	Asyntho 5W-30
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
Change every 30000 km/ 24 months		
Helar SP LL-03 5W-30		
PRODUCT RECOMMENDATION 1		
Extended drain (max)		Moderate
USE		CLIMATE
ENGINE CBZB Capacity: 3,7 liter (Service fill)		

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 0AJ 6/1 Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

TRANSAXLE SEMI-AUTOMATIC 0AM 7/ Capacity: 1,7 liter	1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	

HYDRAULIC ACTUATION GEARBOX		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

AUDI (EU) A3, S3, RS 3 8P A3 1.2 TFSI (2010-2013)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		
Check every 24 months/ 30000 km	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.