

AUDI (EU) A4, S4, RS 4 8D A4 1.6 (75 KW) (2000-2001)



ENGINE ALZ
Capacity: 3,5 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Helar 0W-40

Change every 15000 km/ 12 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Presteza MSP 5W-30	

Change every 15000 km/ 12 months

TRANSAXLE MANUAL 012 / 01W / 0A9 5/1
Capacity: 2,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Check every 30000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Change every 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

AUDI (EU) A4, S4, RS 4 8D A4 1.6 (75 KW) (2000-2001)

**COOLING SYSTEM**

Capacity: 7,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 12	Coolant SP 12 EVO	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.