

# AUDI (EU) A5, S5, RS 5 8T S5 4.2 FSI QUATTRO (2007-2012)



**ENGINE CAUA**  
Capacity: 8,8 liter

| USE                  | CLIMATE  |
|----------------------|----------|
| Extended drain (max) | Moderate |

PRODUCT RECOMMENDATION 1

**Helar SP LL-03 5W-30**

*Change every 30000 km/ 24 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Helar 0W-40**

PRODUCT RECOMMENDATION 2

**Emperol 5W-40**

PRODUCT RECOMMENDATION 3

**Asyntho 5W-30**

*Change every 15000 km/ 12 months*

**DIFFERENTIAL FROM AUTOMATIC**  
Capacity: 1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

**DIFFERENTIAL REAR 0BC**  
Capacity: 0,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

*Check every 24 months/ 30000 km*

**TRANSAXLE MANUAL/TRANSFERBOX 0B4 6/1**  
Capacity: 3,8 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**SP Gear 1011**

PRODUCT RECOMMENDATION 2

**Syngear TDL 75W-90**

*Check every 24 months/ 30000 km*

# AUDI (EU) A5, S5, RS 5 8T S5 4.2 FSI QUATTRO (2007-2012)



## TRANSFERBOX FROM AUTOMATIC

Capacity: 0,5 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Gear LS 1015</b>   |  |          |

## TRANSMISSION AUTOMATIC 0B6 6/1

Capacity: 9-10,4 liter (Dry fill)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 2034</b>     |  |          |

## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE                              |  | CLIMATE  |
|----------------------------------|--|----------|
| Normal                           |  | Moderate |
| PRODUCT RECOMMENDATION 1         |  |          |
| <b>Drauliquid-LV Super DOT 4</b> |  |          |

*Change every 24 months*

## POWER STEERING

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 3013</b>     |  |          |

*Check every 24 months/ 30000 km*

## COOLING SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 12 EVO</b> |  |          |

*Check every 24 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.