AUDI (EU) A6, S6, RS 6 4G A6 2.0 TFSI (155 KW) (2011-2012)



ENGINE CAEB, CDNC, CPMA Capacity: 4,6 liter		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
Helar SP LL-03 5W-30		
Change every 30000 km/ 24 months	•	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30
Change every 15000 km/ 12 months		

DIFFERENTIAL CVT Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

TRANSMISSION CVT 0AW 1/1 Capacity: 8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4016	
Change every 60000 km	

TRANSMISSION S TRONIC CLUTCH PART 0B5 (DL501) Capacity: 7,5 liter (Dry fill, with oil cooler), Capacity: 7 liter (Dry fill, without oil cooler), Capacity: 5,5-6 liter (Service fill)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2072		
Change every 60000 km		

AUDI (EU) A6, S6, RS 6 4G A6 2.0 TFSI (155 **KW)** (2011-2012)



TRANSMISSION S TRONIC TRANSMISSION PART 0B5 (DL501) 7/1 Capacity: 4,35 liter (Dry fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		
Change every 60000 km		

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Check every 30000 km/ 12 months, change every 24 months	

Check every 30000 km/12 months, change every 24 months

COOLING SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Check every 24 months/ 30000 km	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.