Change every 15000 km/ 12 months

AUDI (EU) A8, S8 4E A8 3.0 TDI DPF QUATTRO (155 KW) (2005-2010)



| ENGINE BNG Capacity: 8,2 liter | | |
|-----------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Extended drain (max) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Helar SP LL-03 0W-30 | Helar SP LL-03 5W-30 | |
| Change every 30000 km/ 24 months | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Helar SP LL-03 0W-30 | Helar SP LL-03 5W-30 | |

| DIFFERENTIAL FRONT Capacity: 1,1 liter | | | |
|---|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Gear 1011 | Syngear TDL 75W-90 | | |

| DIFFERENTIAL REAR 01R Capacity: 1,5 liter | | | |
|--|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| SP Gear 1011 | Syngear TDL 75W-90 | | |

| TRANSAXLE AUTOMATIC 09L 6/1 Capacity: 9,8 liter (Initial fill), Capacity: 8 liter (Overhaul capacity) | | |
|---|-----------------------------|--|
| | CLIMATE | |
| | Moderate | |
| | | |
| | | |
| | B liter (Overhaul capacity) | |

AUDI (EU) A8, S8 4E A8 3.0 TDI DPF QUATTRO (155 KW) (2005-2010)



| TRANSFERBOX FROM AUTOMATIC Capacity: 0,55 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Gear LS 1015 | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 1 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid-LV Super DOT 4 | |
| | • |

Check every 30000 km/ 12 months, change every 24 months

| HYDRAULIC SYSTEM POWER STEERING/LEVELLING USE CLIMATE | | |
|---|----------|--|
| | | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| SP Fluid 3013 | | |

| COOLING SYSTEM Capacity: 15,8 liter | |
|-------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 12 EVO | |
| Check every 60000 km/12 months | • |

Check every 60000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.