

AUDI (EU) TT, TTS, TT RS 8J3 TT RS PLUS 2.5 TFSI QUATTRO (2011-2014)

**ENGINE CEPB**

Capacity: 5,7-6,5 liter (Service fill)

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30*Change every 30000 km/ 24 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30*Change every 15000 km/ 12 months***BEVEL GEAR**

Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Check every 24 months/ 30000 km***DIFFERENTIAL REAR**

Capacity: 0,95 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Check every 24 months/ 30000 km***TRANSAXLE MANUAL 0A6 6/1**

Capacity: 2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

PRODUCT RECOMMENDATION 2

SP Gear 5015*Check every 60000 km/ 36 months*

AUDI (EU) TT, TTS, TT RS 8J3 TT RS PLUS

2.5 TFSI QUATTRO (2011-2014)



TRANSAXLE SEMI-AUTOMATIC 0BH 7/1

Capacity: 7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		

HALDEX-CLUTCH

Capacity: 0,72 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 6033		

Check every 24 months/ 30000 km

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 48 months/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.