AUDI (EU) TT, TTS, TT RS ROADSTER 8J9 TT ROADSTER 2.0 TFSI QUATTRO (147 KW)



(2008-2010)

ENGINE BWA, CAWB, CBFA, CCZA Capacity: 4,5-4,6 liter (Service fill)			
USE		CLIMATE	
Extended drain (max)		Moderate	
PRODUCT RECOMMENDATION 1			
Helar SP LL-03 5W-30			
Change every 30000 km/24 months			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30	
Change every 15000 km/ 12 months			

BEVEL GEAR Capacity: 0,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

DIFFERENTIAL REAR Capacity: 0,95 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

TRANSAXLE MANUAL 02Q 6/1 Capacity: 2,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 60000 km/ 36 months		

PRODUCT RECOMMENDATION

AUDI (EU) TT, TTS, TT RS ROADSTER 8J9 TT ROADSTER 2.0 TFSI QUATTRO (147 KW)



(2008-2010)

(2000 2010)		
TRANSAXLE SEMI-AUTOMATIC 02E 6/2 Capacity: 6,9 liter (Dry fill), Capacity: 5,5 li		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		
Change every 60000 km		
HYDRAULIC ACTUATION CONVERTIBI	F ROOF	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
HALDEX-CLUTCH Capacity: 0,85 liter (Dry fill), Capacity: 0,7	liter (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 6033		
HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change every 24 months		
COOLING SYSTEM Capacity: 0-0 liter (Between min and max.		
use		CLIMATE

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Normal

PRODUCT RECOMMENDATION 1
Coolant SP 12 EVO

Check every 48 months/ 60000 km

Moderate