BMW (USA) 1 SERIES E82 128I N51 (2008-2013)



ENGINE N51 Capacity: 6,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR AS OF 07/2011 Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

DIFFERENTIAL REAR UP TO 07/2 Capacity: 1 liter	2011		
use Normal		сымате Moderate	
			PRODUCT RECOMMENDATION 1
SP Gear 1011	Syngear TDL 75W-90		

TRANSMISSION AUTOMATIC GM GA6L45R (GM6) 6/1 Capacity: 9-10 liter				
USE	CLIMATE			
Normal	Moderate			
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Change every 100000 miles	·			

TRANSMISSION MANUAL Getra Capacity: 1,6 liter (Initial fill), Capac		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

BMW (USA) 1 SERIES E82 128I N51 (2008-2013)



HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change every 24 months		
POWER STEERING WITH ACTIVE FROM	NT STEERING/ ACTIVE ROLL STABILIZAT	TION
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
POWER STEERING SEPARATE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
COOLING SYSTEM Capacity: 8,2 liter (+ manual transmission/	transaxle), Capacity: 8,4 liter (with automation	c transmission)
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Coolant SP 11