

**BMW (EU) 3 SERIES E30 324TD (1988-1991)****ENGINE**

Capacity: 5,5 liter, Filter capacity: 1,25 liter

USE		CLIMATE
Flexible (on board maintenance system)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Emperol 5W-50</b>	<b>Classic Racing Oil 15W-50</b>	<b>Bi-Turbo 15W-40</b>

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Emperol 10W-40</b>		

USE		CLIMATE
Flexible (on board maintenance system)		Cold
PRODUCT RECOMMENDATION 1		
<b>Asyntho 5W-30</b>		

**DIFFERENTIAL REAR**

Capacity: 1,7 liter

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
<b>Gearlube GL-5 80W-90</b>		

**TRANSMISSION AUTOMATIC ZF 4HP22 4/1**

Capacity: 3 liter

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

**TRANSMISSION MANUAL 5/1**

Capacity: 1,15 liter

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 12 months*

**POWER STEERING SEPARATE SYSTEM**

Capacity: 1,2 liter

USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
<b>ATF Dexron II-D</b>		

**COOLING SYSTEM**

Capacity: 12 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Coolant SP 11</b>		

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*