PRODUCT RECOMMENDATION

BMW (EU) 3 SERIES E30 325IX (1988-1991)



ENGINE M20B25 Capacity: 4,25 liter, Filter capacity: 0,25 liter			
USE		CLIMATE	
Flexible (on board maintenance systemeters)	em)	Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Bi-Turbo 15W-40	HDX 20W-50		
USE		CLIMATE	
Flexible (on board maintenance systemeters)	em)	Cold	
PRODUCT RECOMMENDATION 1			
Emperol 10W-40			
USE		CLIMATE	
Flexible (on board maintenance systemeters)	em)	Arctic	
PRODUCT RECOMMENDATION 1			
Asyntho 5W-30			

DIFFERENTIAL FRONT Capacity: 0,7 liter		
USE		CLIMATE
Flexible (on board maintenance systemeters)	em)	Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

DIFFERENTIAL REAR Capacity: 1,7 liter		
USE		CLIMATE
Flexible (on board maintenance systemeters)	em)	Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

TRANSFERBOX Capacity: 0,5 liter		
USE		CLIMATE
Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

PRODUCT RECOMMENDATION

BMW (EU) 3 SERIES E30 325IX (1988-1991)



TRANSMISSION AUTOMATIC ZF 4/1 Capacity: 3 liter		
USE		CLIMATE
Flexible (on board maintenance systemeters)	em)	Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

TRANSMISSION MANUAL 5/1 Capacity: 1,25 liter		
USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

HYDRAULIC SYSTEM POWER STEERING/BRAKE BOOSTER		
	CLIMATE	
	Moderate	
em)		CLIMATE

HYDRAULIC BRAKE/CLUTCH SYST	EM		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Change every 12 months

POWER STEERING SEPARATE SYSTEM		
use Flexible (on board maintenance syst	em)	сымате Moderate
PRODUCT RECOMMENDATION 1 ATF Dexron II-D		

BMW (EU) 3 SERIES E30 325IX (1988-1991)



COOLING SYSTEM Capacity: 10,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	
Change every 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.