BMW (EU) 3 SERIES E36 318I (1990-1994)



ENGINE M40 Capacity: 4 liter, Filter capacity: 0,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Emperol 5W-40	Emperol 10W-40
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		

DIFFERENTIAL REAR Capacity: 1,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

DIFFERENTIAL REAR LIMITED SLIP Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	

TRANSMISSION AUTOMATIC WI'Capacity: 3,3 liter, Capacity: 7,8 liter	TH BLACK RATING PLATE GM THM-R1 or (+ torque converter)	(A4S270/310R) 4/1	
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

BMW (EU) 3 SERIES E36 318I (1990-1994)



TRANSMISSION AUTOMATIC WITH Capacity: 3,3 liter, Capacity: 7,8 liter (+	GREEN RATING PLATE GM THM-R1 - torque converter)	(A4S270/310R) 4/1	
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 2032			
TRANSMISSION MANUAL 5/1 Capacity: 1,1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			
HYDRAULIC BRAKE/CLUTCH SYST	EM .		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 24 months			
POWER STEERING SEPARATE SYS Capacity: 1,2 liter	TEM		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
ATF Dexron II-D			
	·		
ODDI IND OVOTEM			
COOLING SYSTEM Capacity: 6,5 liter			
USE		CLIMATE	
Normal		Moderate	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

PRODUCT RECOMMENDATION 1

Change every 24 months

Coolant SP 11