BMW (EU) 3 SERIES E46 328I (1998-2000)



ENGINE M52B28TU Capacity: 6,5 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Helar MSP+ 5W-40

Change every 20000 km/24 months

DIFFERENTIAL REAR Capacity: 1 liter			
USE		CLIMATE	CLIMATE
Flexible (on board maintenance system)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011 Syngear TDL 75W-90			

DIFFERENTIAL REAR LIMITED SLIP Capacity: 1,2 liter		
USE		CLIMATE
Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

TRANSMISSION AUTOMATIC GM A5S 360R/390R 5/1 Capacity: 4 liter, Capacity: 9 liter (+ torque converter)		
USE		CLIMATE
Flexible (on board maintenance system)		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

TRANSMISSION AUTOMATIC ZF 5HP19 (A5S325Z) 5/1		
USE		CLIMATE
Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

BMW (EU) 3 SERIES E46 328I (1998-2000)



TRANSMISSION MANUAL ZF 5/1 Capacity: 1,2 liter		
USE		CLIMATE
Flexible (on board maintenance syst	em)	Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Flexible (max)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 80000 km, change every 24 months

POWER STEERING WITH AFS/ ARS (CHF CAP)			
USE		CLIMATE	
Flexible (on board maintenance syst	em)	Moderate	
PRODUCT RECOMMENDATION 1			
SP Fluid 3013			

POWER STEERING SEPARATE SYSTEM Capacity: 1 liter		
USE	CLIMATE	
Flexible (max)	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 40000 km		

COOLING SYSTEM Capacity: 8,4 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		
Charle avenu 40000 km shanga avenu 40	· · · · · · · · · · · · · · · · · · ·	

Check every 40000 km, change every 48 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.