## BMW (EU) 3 SERIES E90 / E91 / E92 316I (2007-2012)



ENGINE N40/N45
Capacity: 4,25 liter

USE
Flexible (max)

PRODUCT RECOMMENDATION 1
Helar SP LL-03 0W-30

CLIMATE
Moderate

PRODUCT RECOMMENDATION 2
Helar SP LL-03 5W-30

Presteza MSP 5W-30

Change every 25000 km/24 months

DIFFERENTIAL REAR AS OF 07/2011 Capacity: 1 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 1011	Syngear TDL 75W-90			
SP Gear 1011	Syngear TDL 75W-90			

DIFFERENTIAL REAR UP TO 07/2011 Capacity: 1 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 1011	Syngear TDL 75W-90			

TRANSMISSION MANUAL Getrag GS6-17BG/DG 6/1 Capacity: 1,4 liter (Initial fill), Capacity: 1,3 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear 5015				

## BMW (EU) 3 SERIES E90 / E91 / E92 316I (2007-2012)



HYDRAULIC BRAKE/CLUTCH SYSTEM	DSC	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change every 24 months		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		
Change every 12 months		
POWER STEERING WITH AFS/ ARS (CH	IF CAP)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
POWER STEERING SEPARATE SYSTEM	И	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

**Coolant SP 11**