

BMW (EU) 5 SERIES E60 / E61 530D XDRIVE

DPF (2007-2010)

**ENGINE M57TU2**

Capacity: 6,7 liter (Black dipstick (ring)), Capacity: 7,7 liter (Red dipstick (ring))

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Helar MSP+ 5W-40

Change every 30000 km/ 24 months

DIFFERENTIAL FRONT

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

DIFFERENTIAL REAR 215K

Capacity: 1,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

TRANSFERBOX

Capacity: 0,52 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1081		

TRANSMISSION AUTOMATIC ZF 6HP26 6/1

Capacity: 9,4-10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

BMW (EU) 5 SERIES E60 / E61 530D XDRIVE

DPF (2007-2010)


TRANSMISSION MANUAL ZF GS6-53BZ/DZ 6/1

Capacity: 1,9-2,5 liter (Initial fill), Capacity: 1,7-2,3 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

TRANSMISSION MANUAL WITH MTF-LT3 LABEL ZF GS6-53BZ/DZ 6/1

Capacity: 1,9-2,5 liter (Initial fill), Capacity: 1,7-2,3 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

HYDRAULIC BRAKE/CLUTCH SYSTEM DSC

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months
POWER STEERING COMBINED WITH LEVELLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

POWER STEERING SEPARATE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

BMW (EU) 5 SERIES E60 / E61 530D XDRIVE DPF (2007-2010)

**COOLING SYSTEM**

Capacity: 9,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11*Change every 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.