

# BMW (EU) 7 SERIES E32 750I WITH CATALYST (1987-1990)

**ENGINE**

Capacity: 7,5 liter, Filter capacity: 1 liter

| USE                                    |                          | CLIMATE                  |
|--|--------------------------|--------------------------|
| Flexible (on board maintenance system) |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| <b>Emperol 5W-40</b>                   | <b>Asyntho 5W-30</b>     | <b>Emperol 10W-40</b>    |

**DIFFERENTIAL REAR**

Capacity: 1,9 liter

| USE                      |                           | CLIMATE  |
|--------------------------|---------------------------|----------|
| Normal                   |                           | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |          |
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |          |

**TRANSMISSION AUTOMATIC ZF 4/1**

Capacity: 7,5-8,1 liter (+ torque converter), Capacity: 3-3,1 liter (Service fill)

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

**TRANSMISSION MANUAL 5/1**

Capacity: 1,25 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

**HYDRAULIC SYSTEM POWER STEERING/BRAKE BOOSTER/LEVELLING**

Capacity: 3 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>LHM +</b>             |  |          |

# BMW (EU) 7 SERIES E32 750I WITH CATALYST (1987-1990)



## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

*Change every 12 months*

## COOLING SYSTEM

Capacity: 15 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 11</b>     |  |          |

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*