

BMW (EU) 3 SERIES CONVERTIBLE E93

320D EFFICIENTDYNAMICS (2010-2013)



ENGINE N47D20
Capacity: 5,2 liter

| USE | CLIMATE |
|----------------|----------|
| Flexible (max) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|---------------------------|--------------------------|
| Helar SP LL-03 5W-30 | Presteza MSP 5W-30 | Helar MSP+ 5W-40 |

Change every 30000 km/ 24 months

DIFFERENTIAL REAR AS OF 07/2011
Capacity: 1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|---------------------------|--|
| SP Gear 1011 | Syngear TDL 75W-90 | |

DIFFERENTIAL REAR UP TO 07/2011
Capacity: 1 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|---------------------------|--|
| SP Gear 1011 | Syngear TDL 75W-90 | |

TRANSMISSION MANUAL ZF GS6-45BZ/DZ 6/1

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| SP Matic 2072 | | |

BMW (EU) 3 SERIES CONVERTIBLE E93

320D EFFICIENTDYNAMICS (2010-2013)



HYDRAULIC BRAKE/CLUTCH SYSTEM DSC

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*

| USE | CLIMATE |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 12 months*

POWER STEERING WITH ACTIVE FRONT STEERING/ ACTIVE ROLL STABILIZATION

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Fluid 3013

POWER STEERING SEPARATE SYSTEM

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

COOLING SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant SP 11

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.