## BRABUS SLK/CLK SLK 3.8 S (2000-2002)



Helar 0W-40	Emperol 5W-40	Asyntho 5W-30
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE
Bi-Turbo 20W-50		
PRODUCT RECOMMENDATION 1		
Normal		Mediterranean
USE		CLIMATE
ENGINE SLK 320 Capacity: 8 liter		

<b>DIFFERENTIAL REAR</b> Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

DIFFERENTIAL REAR LIMITED SLIP Capacity: 1,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 1071	

<b>TRANSMISSION AUTOMATIC</b> 5/1 Capacity: 7,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 4026	SP Matic 2032		

HYDRAULIC LEVELLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3023		

## BRABUS SLK/CLK SLK 3.8 S (2000-2002)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

POWER STEERING Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 4026	SP Matic 2032	

COOLING SYSTEM Capacity: 9,5 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.