

BUICK (USA / CAN) REGAL EPSILON II

REGAL 2.4L VVT (2013-2014)



ENGINE LEA
Capacity: 4,7 liter

USE	CLIMATE
Flexible (max)	Arctic

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

Change every 12 months

TRANSAXLE AUTOMATIC Hydra-Matic 6T40 6/1
Capacity: 8,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Change every 97500 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Change every 45000 miles

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

POWER STEERING
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

BUICK (USA / CAN) REGAL EPSILON II

REGAL 2.4L VVT (2013-2014)

**COOLING SYSTEM**

Capacity: 7,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15****PRODUCT RECOMMENDATION 2****Coolant SP 15+***Change every 150000 miles/ 60 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.