CADILLAC (EU) CTS(-V) CTS 3.6 V6 (2013-2014)



| ENGINE LFX Capacity: 5,7 liter | |
|---|----------|
| USE | CLIMATE |
| Flexible (max) | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Presteza MSP 5W-30 | |
| Champion avery (15000 kms/ 40 magnifica | |

Change every 15000 km/ 12 months

| DIFFERENTIAL REAR | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube LS 80W-90 |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Gear 1011 | Syngear TDL 75W-90 | Gearlube LS 80W-90 |

Change every 30000 km

| DIFFERENTIAL REAR LIMITED SLI | | |
|-------------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| SP Gear LS 1015 | | |
| USE | CLIMATE | |
| Severe | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| SP Gear LS 1015 | | |
| Change aver (20000 km | | |

Change every 30000 km

CADILLAC (EU) CTS(-V) CTS 3.6 V6 (2013-2014)



| TRANSMISSION AUTOMATIC Hydra-Ma Capacity: 6,3 liter | tic 6L45 6/1 | |
|--|--------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4036 | | |
| Change every 96000 km | | |
| USE | | CLIMATE |
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4036 | | |
| Change every 30000 km | | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Drauliquid DOT 3 | |
| Change every 24 months | |

| COOLING SYSTEM Capacity: 11,3 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15 | Coolant SP 15+ | |
| Change every 250000 km/ 60 mon | ths | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.