

CADILLAC (USA / CAN) CTS(-V) CTS-V 5.7 V8 (2004-2005)



ENGINE LS6
Capacity: 6,2 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Presteza MSP 5W-30	Xedoz FE 5W-30

Change every 12 months

DIFFERENTIAL REAR
Capacity: 1,1-1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

DIFFERENTIAL REAR LIMITED SLIP

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Gear LS 1015	

TRANSMISSION MANUAL 6/1
Capacity: 3,5 liter

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	ATF Almirol

Change every 80000 km

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Change every 40000 km

CADILLAC (USA / CAN) CTS(-V) CTS-V 5.7 V8 (2004-2005)



HYDRAULIC CLUTCH SYSTEM

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
<i>Change every 40000 km</i>		

POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2
<i>Change every 12 months</i>		

COOLING SYSTEM

Capacity: 12,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
<i>Check every 12 months, change every 240000 km/ 60 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.