## CADILLAC (USA / CAN) CTS(-V) CTS-V 6.2 V8 (2010-2010)



ENGINE LSA Capacity: 5,7 liter			
use Flexible (max)		CLIMATE	
		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Presteza MSP 5W-30	Xedoz FE 5W-30		
Change every 40000 km		·	

## **DIFFERENTIAL REAR**

We are unable to give a standard recommendation for this component. Please contact our service department.

<b>TRANSMISSION AUTOMATIC</b> 6L90 6/1 Capacity: 6,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 160000 km	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 80000 km	

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Almirol		
Change every 80000 km		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
ATF Almirol		
Change every 40000 km	'	'

## CADILLAC (USA / CAN) CTS(-V) CTS-V 6.2 V8 (2010-2010)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Change every 40000 km	

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and m	nax.)	
use Severe		CLIMATE
		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Change every 40000 km		'

Change every 40000 km

POWER STEERING			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 2032			

COOLING SYSTEM Capacity: 11,8 liter, Capacity: 2,3 lit	ter (intercooler)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		

Check every 12 months, change every 240000 km/60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.