CHEVROLET (EU) (DAEWOO) CAMARO CAMARO 6.2 V8 (298 KW) (2013-2016)



ENGINE L99 Capacity: 7,6 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 5W-30	
Oh	•

Change every 15000 km/ 12 months

DIFFERENTIAL REAR Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 15000 km/ 12 months	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Change every 30000 km/ 12 months	

DIFFERENTIAL REAR LIMITED SLII Capacity: 0,9 liter, Capacity: 75 CM3 (
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear LS 1015	
Check every 15000 km/ 12 months	

USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear LS 1015	
Change every 30000 km/ 12 months	·

CHEVROLET (EU) (DAEWOO) CAMARO CAMARO 6.2 V8 (298 KW) (2013-2016)



TRANSMISSION AUTOMATIC 6/1 Capacity: 6,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 150000 km	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 30000 km/24 months	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 12 months, change every 24 months	1

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	

COOLING SYSTEM Capacity: 10,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Charle avery 12 months shangs of	250000 leng/ 60 magniths	·	

Check every 12 months, change every 250000 km/60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.