

CHEVROLET (EU) (DAEWOO) CAPTIVA

C100 CAPTIVA 3.2 4WD (2010-2011)

**ENGINE**

Capacity: 7,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar 0W-40****PRODUCT RECOMMENDATION 2****Emperol 5W-40****PRODUCT RECOMMENDATION 3****Asyntho 5W-30***Change every 30000 km/ 12 months***DIFFERENTIAL REAR**

Capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90****TRANSAXLE AUTOMATIC** Aisin Warner 55-51LE 5/1

Capacity: 6,85 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026****TRANSFERBOX**

Capacity: 0,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90**

CHEVROLET (EU) (DAEWOO) CAPTIVA

C100 CAPTIVA 3.2 4WD (2010-2011)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,67 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 48 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,06 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 48 months

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

POWER STEERING

Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 12 months/ 30000 km

CHEVROLET (EU) (DAEWOO) CAPTIVA

C100 CAPTIVA 3.2 4WD (2010-2011)

**COOLING SYSTEM**

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 30000 km/ 12 months, change every 240000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.