

CHEVROLET (EU) (DAEWOO) ESPERO

ESPERO 2.0 (1994-1999)

**ENGINE**

Capacity: 3,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Asyntho 5W-30****PRODUCT RECOMMENDATION 2****Emperol 10W-40****PRODUCT RECOMMENDATION 3****Bi-Turbo 15W-40***Change every 15000 km/ 12 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Asyntho 5W-30****PRODUCT RECOMMENDATION 2****Emperol 10W-40****PRODUCT RECOMMENDATION 3****Bi-Turbo 15W-40***Change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC 4/1**

Capacity: 7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032****PRODUCT RECOMMENDATION 2****ATF Almirol***Check every 15000 km/ 12 months, change every 45000 km/ 36 months***TRANSAXLE MANUAL 5/1**

Capacity: 1,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 5015****PRODUCT RECOMMENDATION 2****Gearlube GL-4 80W***Check every 15000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid DOT 3***Change every 30000 km/ 24 months*

CHEVROLET (EU) (DAEWOO) ESPERO

ESPERO 2.0 (1994-1999)



HYDRAULIC CLUTCH SYSTEM

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

Capacity: 1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 45000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.