

CHEVROLET (EU) (DAEWOO) NUBIRA

NUBIRA 1.8 (2005-2010)

**ENGINE**

Capacity: 3,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 5W-30***Check every 1000 km, change every 15000 km/ 12 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Armado Synth LSP Ultra 5W-30***Check every 1000 km, change every 7500 km/ 6 months***TRANSAXLE AUTOMATIC ZF 4HP16 4/1**

Capacity: 6,7-7,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032***Check every 15000 km/ 12 months***USE**

Severe

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 2032***Check every 15000 km/ 12 months, change every 60000 km***TRANSAXLE MANUAL 5/1**

Capacity: 1,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1011****PRODUCT RECOMMENDATION 2****Syngear TDL 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90***Check every 15000 km/ 12 months*

CHEVROLET (EU) (DAEWOO) NUBIRA

NUBIRA 1.8 (2005-2010)



HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 0,5 liter

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Severe | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

Change every 15000 km/ 12 months

POWER STEERING

Capacity: 1,1 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| SP Matic 2032 | ATF Almirol | ATF Dexron II-D |

Check every 1000 km

COOLING SYSTEM

Capacity: 7,5 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15 | Coolant SP 15+ | |

Check every 15000 km/ 12 months, change every 45000 km/ 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.