CHEVROLET (USA / CAN) EXPRESS GMT610 EXPRESS 5.3 V8 (2010-2014)



ENGINE LMF Capacity: 5,7 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 5W-30	
Change every 7500 miles/ 12 months	

DIFFERENTIAL REAR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 7500 miles	·

TRANSMISSION AUTOMATIC 4L60-E 4/1 Capacity: 4,7 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Check every 7500 miles, change every 97500 miles			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Check every 7500 miles, change every 45000 miles

CHEVROLET (USA / CAN) EXPRESS GMT610 EXPRESS 5.3 V8 (2010-2014)



POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	
Check every 7500 miles	

CLIMATE
Moderate

COOLING SYSTEM Capacity: 11,8 liter, Capacity: 14,6 liter (+ rear heater)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Charles your 7500 miles sharps syon 450000 miles (50 months			

Check every 7500 miles, change every 150000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.