

CHEVROLET (USA / CAN) MALIBU MALIBU

2.5 VVT (2013-2016)



ENGINE LCV
Capacity: 4,7 liter

USE	CLIMATE
Flexible (max)	Arctic

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

Change every 7500 miles/ 12 months

TRANSAXLE AUTOMATIC 6T40 GEN3 (MNH) 6/1
Capacity: 8,12 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Check every 7500 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Check every 7500 miles, change every 45000 miles

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Check every 7500 miles, change every 45000 miles/ 36 months

COOLING SYSTEM

Capacity: 7,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15

PRODUCT RECOMMENDATION 2

Coolant SP 15+

Check every 7500 miles, change every 150000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.