

CHEVROLET (USA / CAN) TAHOE GMT820

TAHOE 5.3 V8 (1999-2001)

**ENGINE LM7**

Capacity: 5,7 liter, Filter capacity: 0,95 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

PRODUCT RECOMMENDATION 2

Emperol 10W-40*Change every 15000 km/ 12 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Avanza MSP 0W-30*Change every 15000 km/ 12 months***DIFFERENTIAL FRONT LIMITED SLIP**

Capacity: 1,66 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 15000 km/ 12 months***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 3,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015*Check every 15000 km/ 12 months***TRANSFERBOX NV 246**

Capacity: 1,9 liter

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 15000 km/ 12 months*

CHEVROLET (USA / CAN) TAHOE GMT820

TAHOE 5.3 V8 (1999-2001)

**TRANSMISSION AUTOMATIC 4L60-E 4/1**

Capacity: 10,6 liter (Overhaul capacity), Capacity: 4,7 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 30000 km/ 24 months, change every 165000 km

TRANSMISSION AUTOMATIC 4L80-E 4/1

Capacity: 12,8 liter (Overhaul capacity), Capacity: 7,3 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

Check every 30000 km/ 24 months, change every 165000 km

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 15000 km/ 12 months, change every 30000 km/ 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Almirol	ATF Dexron II-D	

Check every 15000 km/ 12 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

Change every 15000 km/ 12 months

CHEVROLET (USA / CAN) TAHOE GMT820

TAHOE 5.3 V8 (1999-2001)



COOLING SYSTEM

Capacity: 14,1 liter, Capacity: 12,7 liter (with automatic transmission)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 30000 km/ 24 months, change every 165000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.