

CHEVROLET (USA / CAN) TAHOE GMT820

TAHOE 5.3 V8 (2002-2005)

**ENGINE L59/LM7**

Capacity: 5,7 liter, Filter capacity: 0,95 liter

| USE | CLIMATE |
|----------------|----------|
| Flexible (max) | Moderate |

PRODUCT RECOMMENDATION 1

Asyntho 5W-30*Change every 12 months***DIFFERENTIAL FRONT (4x4)**

Capacity: 1,43-1,73 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90*Check every 12500 km/ 12 months***DIFFERENTIAL FRONT SELECTABLE (4x4)**

Capacity: 1,43-1,73 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 12500 km/ 12 months***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 2,03-2,84 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear LS 1015*Check every 12500 km/ 12 months***DIFFERENTIAL REAR STEERABLE AXLE**

Capacity: 2,03-2,84 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

SP Gear LS 1015*Check every 12500 km/ 12 months*

CHEVROLET (USA / CAN) TAHOE GMT820

TAHOE 5.3 V8 (2002-2005)

**TRANSFERBOX**

Capacity: 1,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 12500 km/ 12 months, change every 83000 km***TRANSFERBOX AUTOMATIC**

Capacity: 1,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Check every 12500 km/ 12 months, change every 83000 km***TRANSMISSION AUTOMATIC 4L60-E 4/1**

Capacity: 10,6 liter (Overhaul capacity), Capacity: 4,7 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 6 months, change every 166000 km***TRANSMISSION AUTOMATIC 4L80-E 4/1**

Capacity: 12,8 liter (Overhaul capacity), Capacity: 7,3 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032

PRODUCT RECOMMENDATION 2

ATF Almirol*Check every 6 months, change every 166000 km***HYDRAULIC BRAKE SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 12500 km/ 12 months*

CHEVROLET (USA / CAN) TAHOE GMT820

TAHOE 5.3 V8 (2002-2005)



POWER STEERING

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Almirol | | |

Check every 12500 km/ 12 months

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------------|--------------------------|---------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| HT Q9 High Grade Grease | Labora Grease | Q5 MP Calcep Grease EP 2 |

Check every 12500 km/ 12 months

COOLING SYSTEM

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15 | Coolant SP 15+ | |

Check every 12500 km/ 12 months, change every 240000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.